

# Dragons Breath Solar

## Bollard lighting

### Dragons Breath Solar bollard light technical values

### High performance ground mounted LED for all applications

#### Lighting features

Led light	1.2w
Luminous flux capacity	280 Lm
Minimum CRI (colour rendering index)	>82
Optic	Asymmetric for lighting
Automatic dimming 30%	100% when triggered
Electrical protection	Short Circuit, Overvoltage, Overcurrent, Overheat
Lifetime	20 years

#### Solar panel

System power	6.5w
System voltage	5v
Cell efficiency	22.5%

#### Battery


Battery	LiFePo4 @ 3.2v (38.4wh)
DOD	6000 cycles DOD 80%
Discharge time on full power	24hrs
Temperature	-15°C ~ + 75°C

#### Photometric features

LED source type	SMD3030
Amount	24 pcs
Colour temperature	3000-5000k
Beam angle	120°
Depreciation factor	L70 > 50,000h
Life	90% > 20 years
Effective	DARK SKY COMPLIANT

#### Constructive features

Body material	Aluminium die casting tempered Glass
Lens material	Tempered glass
Installation	Ground mounted
Dimensions	275mm diameter x 900mm high
Protection grade	IP65
Impact grade	IK10
Weight	12.8kg



**Dragons Breath Solar**  
Tel: 01646 600151  
[info@solar dragons.co.uk](mailto:info@solar dragons.co.uk)

